



Article	C1.02.1435
Series	Standard
Battery Type	Li-ion
Size H × W × L (mm)	4.1 × 50.8 × 69.1
Weight (kg)	0.035
Voltage (V)	3.8
Capacity (mAh)	1900
Capacity (Wh)	7.2
Original Code	B500AE, B500BE, EB-BG357BBE
EAN	6971435201178
Packaging	Electrostatic plastic bag
Life time	24 months / 500 cycles
Warranty	12 months / 300 cycles
Compatibility	SAMSUNG GT-i9190 GALAXY S4
	mini, SCH-i435, GT-i9195, GT- i9198, GT-i9192 GALAXY S4 mini DuoS, SCH-i257 GALAXY S4 mini
	AT&T, SM-G357FZ GALAXY ACE STYLE LTE

MATERIAL SAFETY DATA SHEET

LITHIUM RECHARGEABLE BATTERY C1.02.1435 SAMSUNG GT-i9195 GALAXY S4 mini DuoS NFC 190A.13Q3H

MANUFACTURER

Name of Company: Guangzhou Craftmann Battery Company Limited

Address: China, Guangzhou Science City, Kaiyuan Avenue 11, Building C3, F6

NAME OF PRODUCT

Lithium Rechargeable Battery C1.02.1435 SAMSUNG GT-i9195 GALAXY S4 mini DuoS NFC 190A.13Q3H

SUBSTANCE IDENTIFICATION

Substance: Lithium ion or Lithium polymer rechargeable battery

UN Class: Classified as Lithium ion or Lithium polymer batteries (UN3480), 2022 IATA Dangerous

Goods regulations 63rd edition. Packing Instruction 965 Section 1B is applied. The product is handled as Non-Dangerous Goods by meeting the following requirements. Lithium ion or lithium polymer batteries offered for transport are not subject to other additional requirements of the UN Regulations if they meet the following:

- for cells, the watt-hour rating is not more than 20Wh;
- for batteries, Watt-hour rating is not more than 100Wh.
- each cell or battery is of the type proven to meet the requirements of each test in the UN Manual of Tests and Criteria Part III subsection 38.3.

The Watt-hour rating must be marked on outside of the battery case except those manufactured before1 January 2009 which may be transported without this marking until 31 December 2010.

Cells and batteries must be packed in strong outer packaging that conform to 5.0.2.4, 5.0.2.6.1 and 5.0.2.12.1. And they are out of scope for Special Provision A154 and comply with Special Provision A164.

HAZARDOUS AND TOXICITY CLASS

Class name: Not applicable for regulated class

保密警告

关于往来公函保密

公函信件必须是收到授权的员工,才能阅读。本信函仅适用于收到授权的人员阅读。且信函严禁分发、复制、存储或使用信函以及信函附带的所有资料。

如果您收到此类信函,但怀疑是错收。请立即通知发件人,切勿打开文件。信函信息一旦泄露,您将承担法律民事赔偿责任,我们将会对泄露信息者追究到底。

WARNING

ON THE SECRECY OF CORRESPONDENCE AND PRIVACY

It's a confidential document! Authorization is required to read this document. This document is intended solely for the addressee and may contain confidential information protected by law. If you are not the addressee, its employee or representative, as well as the employee responsible for delivering this document to the addressee, we warn that the distribution, copying, storage or any other use of this document, as well as all materials attached to it, is strictly prohibited. If you receive this document by mistake, please immediately inform the sender and destroy the received copy. Otherwise, you may be subject to civil liability for damages arising from the disclosure of confidential information.



文件		MSDS			
C1.02.1435 SAMSUNG GT-i9195 GALAXY S4 mini DuoS NFC 190A.13Q3H					
日期	模板	页数			
24.08.2022	22Q3H	1/3			



Hazard: It may cause heat generation or electrolyte leakage if battery terminals contact with other metals. Electrolyte is flammable. In case of electrolyte leakage, move the battery from fire immediately.

FIRST AID MEASURES

The product contains organic electrolyte. In case of electrolyte leakage from the battery, actions described below are required. Eye contact: Flush the eyes with plenty of clean water for at least 15 minutes immediately, without rubbing. Take a medical

treatment, if appropriate procedures are not taken, this may cause an eye irritation.

Skin contact: Wash the contact areas off immediately with plenty of water and soap. if appropriate procedures are not taken, this may cause sores on the skin.

Inhalation: Remove to fresh air immediately. Take a medical treatment.

FIRE FIGHTING MEASURES

Extinguishing method: Since vapor, generated from burning batteries may make eyes, nose and throat irritate, be sure to extinguish the fire on the windward side. Wear the respiratory protection equipment in some cases.

Fire extinguishing agent: Plenty of water and alcohol-resistant foam are effective.

MEASURES FOR ELECTROLYTE LEAKAGE FROM THE BATTERY

- Take up with absorbent cloth
- Move the battery away from the fire.

HANDLING AND STORAGE

- When packing the batteries, do not allow battery terminals to contact each other, or contact with other metals. Be sure to
 pack batteries by providing partitions in the packaging box, or in a separate plastic bag so that the single batteries are not
 mixed together.
- Use strong material for packaging boxes during their storage and transportation.
- Do not let water penetrate into packaging boxed during their storage and transportation.
- The batteries will be stored at room temperature.
- Do not store the battery in places of the high temperature exceeding 35°C or under direct sunlight or in front of a stove.
 Please also avoid the places of high humidity. Be sure not to expose the battery to condensation, water drop or not store it under frozen condition.
- Batteries are sure to be packed in such a way as to prevent short circuits under conditions normally encountered in transport.
- Please avoid storing the battery in the places where it is exposed to the static electricity so that no damage will not be caused to the protection circuit of the battery pack.

EXPOSURE CONTROL

Facilities: Provide appropriate ventilation system such as local ventilator in the storage place.

Protective clothing: Gas mask for organic gases, safety goggle, safety glove.

PHYSICAL AND CHEMICAL PROPERTIES OF SINGLE CELL

Appearance: Single cell: Prismatic or Cylindrical cell

Normal Voltage: Single cell: 3.6V-3.85V

STABLITY AND REACTIVITY

Since batteries utilize a chemical reaction they are actually considered a chemical product.

As such, battery performance will deteriorate over time even if stored for a long period of time without being used. In addition, the various usage conditions such as charge, discharge, ambient temperature etc. are not maintained within the specified ranges the life expectancy of the battery may be shortened or the device on which the battery is used may be damaged by electrolyte leakage.

保密警告

关于往来公函保密

公函信件必须是收到授权的员工,才能阅读。本信函仅适用于收到授权的人员阅读。且信函严禁分发、复制、存储或使用信函以及信函附带的所有资料。

如果您收到此类信函,但怀疑是错收。请立即通知发件人,切勿打开文件。信函信息一旦泄露,您将承担法律民事赔偿责任,我们将会对泄露信息者追究到底。

WARNING

ON THE SECRECY OF CORRESPONDENCE AND PRIVACY

It's a confidential document! Authorization is required to read this document. This document is intended solely for the addressee and may contain confidential information protected by law. If you are not the addressee, its employee or representative, as well as the employee responsible for delivering this document to the addressee, we warn that the distribution, copying, storage or any other use of this document, as well as all materials attached to it, is strictly prohibited. If you receive this document by mistake, please immediately inform the sender and destroy the received copy. Otherwise, you may be subject to civil liability for damages arising from the disclosure of confidential information.



文件		MSDS		
C1.02.1435 SAMSUNG GT-i9195 GALAXY S4 mini DuoS NFC				
190A.13Q3H				
日期	模板	页数		
24.08.2022	22Q3H	2/3		



ECOLOGICAL INFORMATION

In case of the worn-out battery was disposed in hand, the battery case may be corroded, and leak electrolyte. But, we have no ecological information.

Heavy metal in battery: Mercury (Hg) and Cadmium (Cd) are neither contained nor used in battery.

DISPOSAL CONSIDERATIONS

When the battery is worn out, dispose of it under the ordinance of each local government or the low issued by relating government. Disposal of worn out battery may be subjected to Collection and Recycling Regulation.

TRANSPORT INFORMATION

During the transportation of a large amount of batteries by ship, trailer or railway, do not leave them in the places of high temperatures and do not allow them to be exposed to condensation.

During the transportation do not allow packages to be fallen down or damaged.

Lithium ion or Lithium polymer batteries identified by manufacturer as being defective for safety reasons, or that have been damaged that have the potential of producing a dangerous evolution of heat, fire or short circuit are forbidden for transport(e.g. those being returned to the manufacturer for safety reasons).

Except when installed in equipment, for air shipment that contain one or more cells or batteries, they are necessary to meet the following items.

- A. Each consignment must be accompanied with a document such as air waybill with an indication that:
 - I. The package contains lithium ion or lithium polymer cells or batteries
 - II. The package must be handled with care and that a flammability hazard exists if the package is damaged.
 - III. Special procedures should be followed in the event the package is damaged, to include in section and repacking if necessary;
 - IV. A telephone number for additional information.
- B. Each package must be labeled with a lithium battery handling label. The width 120mm X 110mm sized lithium battery handling label must be labeled onto the side of a package without bending it.
- C. Each package must be capable of withstanding a 1.2 m drop test in any orientation.
 - V. Damage to cells or batteries contained therein;
 - VI. Shifting of the contents so as to allow battery to battery (or cell to cell) contact;
 - VII. Releaser of contents.
- D. Quantity per package shall not exceed 10kgs.
- E. Each package containing more than four cells or more than two batteries installed in equipment must be complied with above item 1 and 2.

REGULATORY INFORMATION

IATA Dangerous Goods Regulations 63rd Edition Effective 1 January 2022.

ICAO Technical instructions for the safe transport of dangerous goods by air.

保密警告

关于往来公函保密

公函信件必须是收到授权的员工,才能阅读。本信函仅适用于收到授权的人员阅读。且信函严禁分发、复制、存储或使用信函以及信函附带的所有资料。

如果您收到此类信函,但怀疑是错收。请立即通知发件人,切勿打开文件。信函信息一旦泄露,您将承担法律民事赔偿责任,我们将会对泄露信息者追究到底。

WARNING

ON THE SECRECY OF CORRESPONDENCE AND PRIVACY

It's a confidential document! Authorization is required to read this document. This document is intended solely for the addressee and may contain confidential information protected by law. If you are not the addressee, its employee or representative, as well as the employee responsible for delivering this document to the addressee, we warn that the distribution, copying, storage or any other use of this document, as well as all materials attached to it, is strictly prohibited. If you receive this document by mistake, please immediately inform the sender and destroy the received copy. Otherwise, you may be subject to civil liability for damages arising from the disclosure of confidential information.



文件		MSDS		
C1.02.1435 SAMSUNG GT-i9195 GALAXY S4 mini DuoS NFC				
190A.13Q3H				
日期	模板	页数		
24.08.2022	22Q3H	3/3		